



StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 1/23/2019 Revision date: 2/4/2025 Supersedes: 3/1/2024 Version: 1.11

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : StaBil® Fuel Stabilizer – Storage
Synonym : 590025

1.2. Other means of identification

Part numbers : 22204; 22205; 22206; 22207; 22208; 22209; 22211; 22213; 22214; 22215; 22218; 22249;
22280; 22803; 22807; 22812; 22816; 22287;

1.3. Recommended use of the chemical and restrictions on use

Intended for general public
Use of the substance/mixture : Fuel additives
Recommended use : Read label before use.
Restrictions on use : Use per the label directions

1.4. Supplier's details

Manufacturer

Gold Eagle Co.
4400 S. Kildare Avenue
Chicago, Cook, IL 60632
USA
T 773-376-4400

producttechsupport@goldeagle.com - www.goldeagle.com

1.5. Emergency phone number

Emergency number : 1-800-535-5053
For Chemical Emergency Call 24 hours a day, 7 days a week 24hr/day 7days/week
Within USA and Canada: 24 hours a day, 7 days a week
Outside USA and Canada: 24 hours a day, 7 days a week
(collect calls accepted)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids, Category 4	H227	Combustible liquid.
Carcinogenicity, Category 1B	H350	May cause cancer.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hazard statements (GHS US)	: H227 - Combustible liquid H304 - May be fatal if swallowed and enters airways H350 - May cause cancer.
Precautionary statements (GHS US)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P301+P310 - If swallowed: Immediately call a poison center or doctor. P308+P313 - If exposed or concerned: Get medical advice/attention. P331 - Do NOT induce vomiting. P370+P378 - In case of fire: Use appropriate media to extinguish. P403 - Store in a well-ventilated place. P405 - Store locked up. P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	80 - 100*	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Sweetened middle distillate	CAS-No.: 64741-86-2	5 - 10*	Carc. 1B, H350
Solvent naphtha	CAS-No.: 64742-94-5	3 - 7*	Flam. Liq. 2, H225 Asp. Tox. 1, H304
Ethylene glycol monobutyl ether	CAS-No.: 111-76-2	3 - 7*	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Stabil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store in a well-ventilated place. Keep cool. Store locked up.
Packaging materials	: Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol monobutyl ether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL TWA	240 mg/m ³
	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
----------------------------------	--

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: red
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: Not Determined
Flash point	: 180 °F
Relative evaporation rate (ether=1)	: > 1
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 97 mm Hg
Relative vapor density at 20 °C	: > 1
Relative density	: 0.8
Solubility	: Water: < 0.1 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 3 mm ² /s (40 °C)
Explosion limits	: Lower explosion limit: 7 Upper explosion limit: 0.8
Explosive properties	: Not explosive.
Oxidizing properties	: Not oxidising.
Particle characteristics	: No data available

Sweetened middle distillate	
Particle characteristics	No data available

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Distillates (petroleum), hydrotreated light	
Particle characteristics	No data available

Ethylene glycol monobutyl ether	
Particle characteristics	No data available

Solvent naphtha	
Particle characteristics	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 100

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethylene glycol monobutyl ether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 oral	1414 mg/kg body weight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Ethylene glycol monobutyl ether (111-76-2)	
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
ATE US (oral)	1414 mg/kg body weight
ATE US (gases)	450 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer.

Ethylene glycol monobutyl ether (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

StaBil® Fuel Stabilizer – Storage	
Viscosity, kinematic	3 mm ² /s (40 °C)

Sweetened middle distillate (64741-86-2)	
Viscosity, kinematic	No data available

Distillates (petroleum), hydrotreated light (64742-47-8)	
Viscosity, kinematic	0.9 mm ² /s

Ethylene glycol monobutyl ether (111-76-2)	
Viscosity, kinematic	3.49 mm ² /s (25 °C)

Solvent naphtha (64742-94-5)	
Viscosity, kinematic	No data available

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : Risk of lung edema.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Ethylene glycol monobutyl ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	911 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

StaBil® Fuel Stabilizer – Storage	
Persistence and degradability	Not rapidly degradable
Sweetened middle distillate (64741-86-2)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Not rapidly degradable
Ethylene glycol monobutyl ether (111-76-2)	
Persistence and degradability	Readily biodegradable in water.
Solvent naphtha (64742-94-5)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Ethylene glycol monobutyl ether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)
Partition coefficient n-octanol/water (Log Kow)	0.83
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Ethylene glycol monobutyl ether (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No.(DOT)	: Not regulated
UN-No. (TDG)	: Not regulated
UN-No. (IMDG)	: Not regulated
UN-No. (IATA)	: Not subject

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Not regulated
Proper Shipping Name (TDG)	: Not regulated
Proper Shipping Name (IMDG)	: Not regulated
Proper Shipping Name (IATA)	: Not subject

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not regulated

TDG
Transport hazard class(es) (TDG) : Not regulated

IMDG
Transport hazard class(es) (IMDG) : Not regulated

IATA
Transport hazard class(es) (IATA) : Not subject

14.4. Packing group

Packing group (DOT)	: Not regulated
Packing group (TDG)	: Not regulated
Packing group (IMDG)	: Not regulated
Packing group (IATA)	: Not subject

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

Special transport precautions : Not regulated for transport in Non Bulk Container sizes of 119 gallons or less. Bulk UN number is 1268

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

IATA
Not subject

StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 15 Regulatory information

15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Sweetened middle distillate	64741-86-2	Present	Active	
Distillates (petroleum), hydrotreated light	64742-47-8	Present	Active	
Ethylene glycol monobutyl ether	111-76-2	Present	Active	
Solvent naphtha	64742-94-5	Present	Active	

15.2. International regulations

CANADA

Sweetened middle distillate (64741-86-2)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Ethylene glycol monobutyl ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Solvent naphtha (64742-94-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Solvent naphtha (64742-94-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 2/4/2025

Issue date : 1/23/2019


StaBil® Fuel Stabilizer – Storage

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H350	May cause cancer.

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



- Hazard Rating Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
- Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
- Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
- Personal protection : B - Safety glasses, Gloves

Indication of changes:		
Section	Changed item	Comments
1		Added part numbers: 22209; 22258
2	GHS-US classification	Modified

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.